

Package ‘reactRouter’

April 29, 2025

Type Package

Title 'React Router' for 'shiny' Apps and 'Quarto'

Version 0.1.0

Maintainer Felix Luginbuhl <felix.luginbuhl@protonmail.ch>

Description You can easily share url pages using 'React Router' in 'shiny' applications and 'Quarto' documents. The package wraps the 'react-router-dom' 'React' library and provides access to hash routing to navigate on multiple url pages.

License MIT + file LICENSE

Encoding UTF-8

Depends R (>= 3.4)

Imports htmltools, shiny, shiny.react, checkmate

Suggests testthat (>= 3.0.0), chromote (>= 0.1.1.9001), shinytest2, knitr, rmarkdown

RoxygenNote 7.3.2

URL <https://felixluginbuhl.com/reactRouter/>

BugReports <https://github.com/lgnbhl/reactRouter/issues>

Config/testthat/edition 3

VignetteBuilder knitr

NeedsCompilation no

Author Felix Luginbuhl [aut, cre] (<<https://orcid.org/0009-0008-6625-2899>>),
Shopify Inc. [ctb, cph] (Shopify Inc. template
<<https://reactrouter.com/>>)

Repository CRAN

Date/Publication 2025-04-29 09:10:08 UTC

Contents

HashRouter	2
Link	2

2

Link

MemoryRouter

Navigate

NavLink

Outlet

reactRouterDependency

Route

Routes

Index

7

HashRouter	<i>HashRouter</i>
------------	-------------------

Description

<https://reactrouter.com/6.30.0/router-components/hash-router>

Usage

HashRouter(...)

Arguments

... Props to pass to element.

Value

A HashRouter component.

Link	<i>Link</i>
------	-------------

Description

<https://reactrouter.com/6.30.0/components/link>
<https://reactrouter.com/en/main/components/link>

Usage

Link(...)

Link.shinyInput(inputId, ...)

updateLink.shinyInput(
 session = shiny::getDefaultReactiveDomain(),
 inputId,
 ...
)

Arguments

...	Props to pass to element.
inputId	ID of the component.
session	Object passed as the 'session' argument to Shiny server.

Value

A Link component.

MemoryRouter

*MemoryRouter***Description**

<https://reactrouter.com/6.30.0/router-components/memory-router>

Usage

```
MemoryRouter(...)
```

Arguments

...	Props to pass to element.
-----	---------------------------

Value

A MemoryRouter component.

Navigate

*Navigate***Description**

<https://reactrouter.com/6.30.0/components/navigate>

Usage

```
Navigate(...)
```

Arguments

...	Props to pass to element.
-----	---------------------------

Value

A Navigate component.

NavLink*NavLink*

Description

<https://reactrouter.com/6.30.0/components/nav-link>
<https://reactrouter.com/en/main/components/nav-link>

Usage

```
NavLink(...)  
  
NavLink.shinyInput(inputId, ...)  
  
updateNavLink.shinyInput(  
  session = shiny::getDefaultReactiveDomain(),  
  inputId,  
  ...  
)
```

Arguments

...	Props to pass to element.
inputId	ID of the component.
session	Object passed as the ‘session‘ argument to Shiny server.

Value

A NavLink component.

Outlet*Outlet*

Description

<https://reactrouter.com/6.30.0/components/outlet>

Usage

```
Outlet(...)
```

Arguments

...	Props to pass to element.
-----	---------------------------

Value

A Outlet component.

reactRouterDependency	<i>react-router-dom JS dependency</i>
-----------------------	---------------------------------------

Description

react-router-dom JS dependency

Usage

reactRouterDependency()

Value

HTML dependency object.

Route	<i>Route</i>
-------	--------------

Description

<https://reactrouter.com/6.30.0/components/route>

Usage

Route(...)

Arguments

... Props to pass to element.

Value

A Route component.

Routes	<i>Routes</i>
--------	---------------

Description

<https://reactrouter.com/6.30.0/components/routes>

Usage

Routes(...)

Arguments

... Props to pass to element.

Value

A Routes component.

Index

HashRouter, [2](#)

Link, [2](#)

MemoryRouter, [3](#)

Navigate, [3](#)

NavLink, [4](#)

Outlet, [4](#)

reactRouterDependency, [5](#)

Route, [5](#)

Routes, [6](#)

updateLink.shinyInput (Link), [2](#)

updateNavLink.shinyInput (NavLink), [4](#)